

GRADEN



GBS1200 VERTICUTTER



GBS1200 VERTICUTTER

SPECIFICATIONS

DRIVE BELTS	AX40 Dayco Super 2 Series 6 per machine
GEARBOX	Comer T27A Increasing Gearbox
TRACTOR	20hp +
WHEELS	4.10/3.50-4 tube type slick tires 4 per machine heavy duty bearings in rims
CUTTING DEPTH	variable from 0 to 1.75" (45mm)
CUTTING WIDTH	48" (1200mm)
WIDTH	41" (1050mm)
LENGTH	61" (1540mm)
HEIGHT	20" (500mm)
WEIGHT	620lbs (280kg)

BLADES

standard blade width and spacing
39 x 5/64" (2mm) blades at 1 1/4" (30mm) spacing

optional blade widths
3/64" (1mm) and 1/8" (3mm)

optional variable spacing

tempered steel blades with eight tungsten tips
per blade

blades fitted in reverse rotation to slice cleanly
through the turf

deep scalloped design to prevent blades from
becoming clogged

A tractor mounted 48" (1200mm) straight reel
Graden sporting 39 blades, this powerful machine is
ideal for flat areas including sports fields, cricket
squares, tennis courts, golf tees, relatively flat greens
and approaches.



The GBS1200 performs powerful, efficient and effective verticutting.



PTO safety cover



Simple depth adjustment



A bottom view of the GBS1200 shows its standard 39 blade setup.

GRADEN INDUSTRIES PTY LTD
26-28 Scammel Street, Cambellfield
Victoria 3061, Australia
tel: 61 3 9305 3400
fax: 61 3 9305 3995
email: info@graden.com.au
www.graden.com.au
contact: Graham Dryden

GRADEN USA, INC.
7309 Capehart Road
Richmond, Virginia
tel: 804 249 9950
fax: 804 249 9951
email: info@gradenusa.com
www.gradenusa.com
contact: Matt Neal

