

GRADEN



GS04 VERTICUTTER



GS04 VERTICUTTER

SPECIFICATIONS

ENGINE	Honda 13hp - GX390 unleaded petrol
DRIVE	HYDROSTATIC forward/reverse variable speed
WHEELS	front - 15 x 6.00-6 tube type rear - 6" (150mm) solid rubber
CUTTING DEPTH	variable from 0 to 1.5" (40mm)
CUTTING WIDTH	16" (400mm)
WIDTH	33" (840mm)
LENGTH	59" (1500mm)
HEIGHT	41" (1040mm)
WEIGHT	360lbs (165kg)

BLADES

standard blade width and spacing
15 x 5/64" (2mm) blades at 1" (26mm) spacing

optional blade widths
3/64" (1mm) and 1/8" (3mm)

optional variable spacing

tempered steel blades with eight tungsten tips
per blade

blades fitted in reverse rotation to slice cleanly
through the turf

deep scalloped design to prevent blades from
becoming clogged

The original Graden, this tried and tested machine has proven to be extremely durable while providing excellent results. It is ideal for anywhere you need a Graden including golf greens, tees, approaches, cricket squares, bowling greens, tennis courts and lawns.



Turf tires and swivel wheels maximize traction and maneuverability.



A single knob provides simple depth adjustment.
A spring assists in lifting the machine.

GRADEN INDUSTRIES PTY LTD
26-28 Scammel Street, Camberfield
Victoria 3061, Australia
tel: 61 3 9305 3400
fax: 61 3 9305 3995
email: info@graden.com.au
www.graden.com.au
contact: Graham Dryden

GRADEN USA, INC.
7309 Capehart Road
Richmond, Virginia
tel: 804 249 9950
fax: 804 249 9951
email: info@gradenusa.com
www.gradenusa.com
contact: Matt Neal

