

Increase mulch bonding and adhesiveness with  
ProPlus Tackifiers, Soil Stabilization & Dust Control

## Tacking Agent 3® - Soil Stabilization

A Tackifier that requires no cure time!



Tacking Agent 3 is also available in water soluble packets!

Tacking Agent 3 is University tested and proven to control erosion immediately after seeding, no cure time required!

Tacking Agent 3 contains the known flocculant polyacrylamide (PAM) and hydro-colloid polymers for enhanced fiber-to-soil bond.

### Tacking Agent 3 is proven to:

- > No drying time required - no need to be concerned about a 24-hour window
- > Also contains a marker dye to enhance your fiber mulch color
- > Allows for additional visual metering when any product is being applied
- > Improves water holding capacity
- > Reduces soil erosion and runoff immediately after hydro-seeding
- > Its effective at binding straw, it increases the bond and longevity of the tackifier by combining its use with cellulose fiber mulch
- > Combining FiberLock or FiberMax can assist in holding fiber mulch in place even on the steepest slopes

### Application Rates:

#### Typical Application Rate:

- a. **Moderate to 5:1 Slope** - 20lbs per acre
- b. **4:1 to 3:1 Slope** - 30lbs per acre
- c. **3:1 to 2:1 Slope** - 40lbs per acre
- d. **Greater than 2:1 Slope** - 60lbs per acre
- e. **Straw and Hay Mulch Binding** - 30lbs of Tacking Agent 3 and 150lbs of cellulose fiber to 1000 gallons of water/acre

#### Packaging:

4-8lb bags per pallet/60 cases per pallet  
7-3lb water soluble bags per case/56 cases per pallet  
50lb bag/40-50lb bags per pallet

#### Product Contents - Properties:

Materials: Polyacrylamide, acrylamide copolymer, hydro-colloid polymers, marker dye

pH Range: 7.0 +/-0.2

Surface Tension: 73.9 dynes/cm, based on simulated field application after 5 minutes of mechanical agitation

Viscosity: 102 CPS +/- 2, Saybolt value, based on 30 lbs per 1000 gallons of water

University Tested to reduce erosion 68.6% and reduce water runoff 21.7% on a 45% slope without having to cure (dry out) effective immediately after hydroseeding application

### Tacking Agent® 3- Application Tank Rates (Using 30lbs per Acre)

300 gallon	500 gallon	900 gallon	1500 gallon	3000 gallon
3 lbs	5 lbs	10 lbs	15 lbs	30lbs



Profile Products LLC

750 Lake Cook Road - Suite 440  
Buffalo Grove, IL 60089

800-726-6371 • www.profileproducts.com