

XA325

APPLICATOR



INNOVATION FROM WITHIN

Setting the new standard in Hydroseeding Applicators

- Stainless steel mixing tank
- Hydraulic
 - Agitation - variable speed & reversible
 - Pump drive - variable speed & reversible
- 20 hp Honda engine
- 2" x 2" multi-product gear pump
- Industry exclusive 5 point agitator seal assembly
- 4-way lifting pockets
- Oversized sump to allow for maximum emptying of the tank
- Electric hose reel



STAINLESS STEEL
MIXING TANK

20 HP
HONDA ENGINE

INDUSTRY EXCLUSIVE "5 POINT"
AGITATOR SEAL ASSEMBLY

APEXSEEDER.COM

SPECS



Engine	Honda GX-630, 20 hp. air cooled gasoline engine, electric start
Pump	2"x2" gear pump, hydraulically driven with variable speed, hardened wear plates and reverse function
Pump Drive	Hydraulically driven, reversible
Standard Features	<ul style="list-style-type: none"> · 10 gauge stainless steel · Stainless steel tank top and loading hatch · Fully integrated 8 gallon fuel tank · Exclusive five point agitator seal assembly · Liquid recirculation
Nozzles	Complete set of 3 nozzles - one set of long distance, narrow and wide ribbon fan
Options	Electric hose reel with 100' of 1-1/4" hose

	XA325
Tank: Liquid Capacity	325 gal / 1,230 l
Working Capacity	293 gal / 11,09 l
Granular Solids	
Granular Solids	500 lb / 226.75 kg
Fiber Mulch	130 lb / 58.97 kg
Empty Weight	1,915 lb / 868 kg
Approx. Working Weight	4,100 lb / 1,860 kg
Length	90"
Width	47"
Height	50"

*Weights are approximate and do not include any stowed materials.

ENVIRONMENTAL • EQUIPMENT • MATERIALS • TECHNOLOGY

3460 Grant Dr. Lebanon, Ohio 45036
513.686.1330

APEXSEEDER.COM