

www.keyindustries.co.nz

SAFETY DATA SHEET: Bendi 800

1. IDENTIFICATION

Product Name: Bendi 800

Use: Insecticide

Supplier: Key Industries Ltd

Address: P.O. Box 65070, Mairangi Bay, Auckland 0754

Telephone: 09 917 1791 **Emergency Phone:** 027 494 1659

National Poisons Centre: 0800 POISON (0800 764 766)

2. HAZARD IDENTIFICATION

Product is classified as hazardous according to the regulations of the HSNO Act, 1996. Dangerous Good Class 6.1 for transport.

HSNO Approval: HSR000451

Hazard Classifications: 6.1B (oral), 6.1C (inhalation), 6.1D (dermal), 6.9A, 9.1A, 9.3A. 9.4A

Pictograms:







Signal word: DANGER

Hazard Statements:

- H300 Fatal if swallowed.
- H312 Harmful in contact with skin.
- H331 Toxic if inhaled.
- H372 Causes damage to organs (nervous system) through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H431 Very toxic to terrestrial vertebrates
- H441 Vert toxic to terrestrial vertebrates.

Prevention Statements:

- P102 Keep out of reach of children
- P103. Read label before use.
- P260 Do not breathe dust/mist/spray.
- P264 Wash hands and exposed skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves and eye protection.

Response Statements:

- P314 Get medical attention if you feel unwell.
- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor for advice.
- P330 Rinse mouth.
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P312 Call a POISON CENTRE or doctor if you feel unwell.
- P363 Wash contaminated clothing before re-use.

EMERGENCY PHONE: KEY INDUSTRIES LTD Frank Visser, Managing Director: 0274 941 659



www.keyindustries.co.nz

SAFETY DATA SHEET: Bendi 800

P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable to breathing.

P311 Call a POISON CENTRE or doctor.

P391 Collect spillage.

Storage Statements:

P403 +P233

P405 Store locked up.

Disposal Statements:

P501 Dispose of product and containers in accordance with local regulations.

3. COMPOSITION: INFORMATION ON INGREDIENTS

| Ingredients | CAS Number | Concentration (%w/w) |
|-------------------|--------------|----------------------|
| Bendiocarb | 22781-23-3 | 80 |
| Filler/dispersant | Trade secret | 16 |
| Wetting agent | Trade secret | 4 |

4. FIRST AID MEASURES

Consult the National Poisons Information Centre 0800 POISON (0800 764 766) or a doctor in every case of suspected chemical poisoning. Have product label or Safety Data Sheet at hand.

INGESTION: Immediately call POISON CENTRE or doctor for advice. Rinse mouth. Do not induce vomiting unless advised to do so. If at hand, advice may be to give one atropine tablet (0.6 mg) every 5 minutes until dryness of mouth occurs.

SKIN CONTACT: Wash with soap and water. If irritation develops or person feels unwell, obtain medical advice.

EYE CONTACT: Flush with running water for at least 15 minutes. Remove contact lenses if present, and easy to do after 5 minutes before continuing rinsing. If irritation develops, obtain medical assistance.

INHALATION: Remove patient to fresh air and keep at rest until recovered. Call a POISON CENTRE or doctor for medical advice.

First Aid facilities:

Provide eye baths and safety showers close to work areas.

Advice to Doctor:

Bendiocarb is a carbamate insecticide, which is a reversible cholinesterase inhibitor. Atropine, preferably by injection, is an antidote. Additionally, a benzodiazepine e.g. diazepam) should be given in case of seizures/convulsions.

5. FIRE-FIGHTING MEASURES

Flashpoint: Non-flammable.

Suitable extinguishing media: Water fog, fine water spray, carbon dioxide, dry chemical, foam.

Hazards from combustion products: At temperatures above 125 °C will evolve toxic fumes of methyl isocyanate. At temperatures above 125 °C will evolve toxic fumes of methyl isocyanate.

Precautions for fire fighters and special protective equipment: Self-contained breathing apparatus with full face-piece and protective clothing. Cool fire exposed containers with water spray.

Hazchem Code: 2X

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures:

Wear appropriate personal protection equipment to prevent exposure by inhalation, and to skin and eyes. Avoid dust generation. Ensure adequate ventilation. Wear approved respirator where mist or dust of unknown concentration may be generated. Self-contained breathing apparatus is recommended. Contain spillage and prevent from entering drains, sewer or any water course.

Methods and materials for containment

Dyke and contain solid or liquid with sand, earth, sawdust or vermiculite and transfer liquid and solids separately to labelled containers for recovery or disposal. Clean up and report spills immediately. Keep spills out of sewers and open bodies of water. In event of spillage contaminating a water-course, notify the Police, local Health Protection Officer and Council. Clean contaminated surfaces with water.

EMERGENCY PHONE: KEY INDUSTRIES LTD Frank Visser, Managing Director: 0274 941 659



www.keyindustries.co.nz

SAFETY DATA SHEET: Bendi 800

7. HANDLING AND STORAGE

Precautions for safe handling: Certified Handler required. Read product label and this Safety Data Sheet before use. Keep out of reach of children. Avoid breathing dust or mist/aerosol. Avoid contact with skin or eyes. Observe good personal hygiene practices and recommended procedures including wearing of personal protection equipment. Wash hands and exposed skin thoroughly with soap and water after handling.

Conditions for safe storage: Keep out of reach of children. Store locked up. Do store for prolonged periods in direct sunlight. Avoid temperatures below 0°C and above 30°C. Avoid contamination of and with other products.

Incompatible materials: Not specified.

Other: Changing out of work clothing and showering recommended at the end of each work shift. Wash work clothes separately from other household clothing.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Health Exposure Standards: Workplace Exposure Standards (WES), have not been set by Worksafe for compounds in this

substance:

Particulates (not otherwise classified) WES-TWA 10 mg/m³
Respirable dust WES-TWA 3 mg/m³

Biological limit values: None established

Engineering Controls:

Ventilation: Use outdoors or in a well-ventilated area.

Personal Protective Equipment:

Respiratory Protection: Respiratory protection may be necessary under certain use conditions. Under such conditions, an approved respirator or disposable face mask according to local standards, must be worn.

Eye Protection: Wear safety goggles or face shield.

Skin/ Body Protection: Wear chemical resistant elbow length gloves (rubber, neoprene, nitrile or equivalent), waterproof boots, protective clothing, e.g. overalls with long sleeves buttoned at neck and wrist, long pants).

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Off-white powder Odour Almost no odour Odour threshold Not determined

pH ~7 (as 1% dilution in water)

Melting/Freezing point 0 C

Boiling Point/Range 0 C

Flash Point 0 C

Flammability (solid, gas)

Upper/lower flammability/explosive limits

Not determined

Not applicable

Not applicable

30 g/m³

Vapour Pressure mm Hg @ 20°C

Vapour Density kPa @ 20°C

Relative density

Solubilities

Not determined

Not determined

Suspension in water

Partition coefficient: n-octanol/water

Autoignition Temperature °C

Not determined

Decomposition Temperature °C Not determined Kinematic viscosity Not determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions. Fine dust may form explosive mixture in air.

EMERGENCY PHONE: KEY INDUSTRIES LTD Frank Visser, Managing Director: 0274 941 659



www.keyindustries.co.nz

SAFETY DATA SHEET: Bendi 800

Conditions to avoid: Heating, contact with oxidizing agents and sources of ignition.

Hazardous decomposition products: At temperatures above 125 °C will evolve toxic fumes of methyl isocyanate.

Hazardous reactions: None specified.

11. TOXICOLOGICAL INFORMATION

Toxicity classifications determined by assessment of the components in the formulated mixture.

Acute toxicity: Classified as highly toxic if swallowed, toxic if inhaled and harmful by contact with skin.

Aspiration hazard: Not classified as an aspiration hazard. **Respiratory irritation:** Not classified as respiratory irritant. **Skin corrosion/irritation:** May be irritating to skin.

Serious eye damage/irritation: Mildly irritating. Symptoms may be tearing and blurred vision.

Respiratory or skin sensitization: Not classified as a sensitizer.

Germ cell mutagenicity: Not classified.

Carcinogenicity: Not classified.
Reproductive toxicity: Not classified.

Specific organ toxicity: Causes damage to blood and haematopoietic system by repeated or prolonged exposure. May have

cumulative poisoning effects. Cholinesterase inhibition.

Narcotic effects: Not classified.

Toxicological Information:

Bendiocarb Oral, guinea pig, LD₅₀ 25 mg/kg

Inhalation, rat, LC₅₀ 0.55 mg/L Dermal, rat, LD₅₀ 566 – 800 g/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity: This mixture is classified as toxic to aquatic life with long lasting effects. Do not contaminate waterways, sewers, or drains when disposing of product or wash water from equipment.

Persistence and degradability: No specific information available for mixture. Bendiocarb is not expected to rapidly degrade.

Potential to be bioaccumulative: No specific information available for mixture.

Mobility in soil: Not soluble in water.

Other adverse effects: No information available

Ecotoxicological Information:

Bendiocarb Sheepshead minnow, LC₅₀ (96 hr) 0.86 mg/L

Daphnia sp., EC₅₀ (48 hr) 0.16 mg/L Bobwhite quail, LC₅₀ 19 mg/kg Honey bee, LD₅₀ 0.1 μ g/bee

Environmental Exposure Limits (EEL's): Not set.

13. DISPOSAL CONSIDERATIONS

Disposal Methods: Ensure container is empty before disposal to landfill. For HDPE containers, triple rinse or preferably pressure rinse with water. Use rinsings in preparing the diluted solution.

Waste should be disposed of to an approved waste disposal facility or by burying at an approved site. Do not burn product or containers.

Ensure disposal of containers and product is in compliance with requirements of national and local authorities.

EMERGENCY PHONE: KEY INDUSTRIES LTD Frank Visser, Managing Director: 0274 941 659



www.keyindustries.co.nz

SAFETY DATA SHEET: Bendi 800

14. TRANSPORT INFORMATION

| Road and Rail Transport | | Marine Transport | | Air Transport | |
|-------------------------|--|-------------------------|--|-------------------------|--|
| UN No. | 2757 | UN No. | 2757 | UN No. | 2757 |
| Proper Shipping Name | CARBAMATE PESTICIDE. SOLID, TOXIC (BENDIOCARB MIXTURE) | Proper Shipping Name | CARBAMATE PESTICIDE. SOLID, TOXIC (BENDIOCARB MIXTURE) | Proper Shipping Name | CARBAMATE PESTICIDE. SOLID, TOXIC (BENDIOCARB MIXTURE) |
| DG Class | 6.1 | DG Class | 6.1 | DG Class | 6.1 |
| Sub. Risk | | Sub. Risk | | Sub. Risk | |
| Pack Group | II | Pack Group | II | Pack Group | II |
| Hazchem | 2X | Hazchem | 2X | | |

Marine Pollutant: Yes

Dangerous Goods Segregation

This product is classified as a Dangerous Good Class 6.1 for Transport.

Please consult the Land Transport Rule: Dangerous Goods 2005, and NZS 5433:2012 Transport of Dangerous Goods on Land for information.

15. REGULATORY INFORMATION

HSNO Act 1996

Country: New Zealand

Inventory: NZ Inventory of Chemicals

Status: Components listed

EPA New Zealand Approval Code: HSR000451

HSNO Controls: Refer to www.epa.govt.nz and www.worksafe.govt.nz for information on Default and Additional Controls, HS

Notices and HSW (Hazardous Substances) regulations.

Certified Handler: Required

ACVM Act 1997

Registration Number: Not required (exempt product).

16. OTHER INFORMATION

Date of Issue: 8th August 2018. Reasons for Issue: New SDS.

Replaces:

Abbreviations:

EPA New Zealand Environmental Protection Authority

GHS Global Harmonised System

HSIS Hazardous Substance Information System
HSNO Hazardous Substances and New Organisms
NZIOC New Zealand Inventory of Chemicals

STEL Short Term Exposure Limit (15 minute exposure period)
TWA Time-Weighted Average (8 hours exposure period)

WES Workplace Exposure Standard

References:

EPA <u>www.epa.govt.nz</u>
Worksafe NZ www.worksafe.govt.nz

EMERGENCY PHONE: KEY INDUSTRIES LTD Frank Visser, Managing Director: 0274 941 659



www.keyindustries.co.nz

SAFETY DATA SHEET: Bendi 800

Supplier Safety Data Sheets

Other:

The information contained herein is given in good faith but no warranty, expressed or implied is made.

End of safety data sheet

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the supplier's knowledge. Each user should read this SDS and consider the information in the context of how the product will be handled and used in the workplace. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses, but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product. For further information, please contact Key Industries Limited.

EMERGENCY PHONE: KEY INDUSTRIES LTD Frank Visser, Managing Director: 0274 941 659