

GRADEN



CSI CONTOUR SAND INJECTION



GRADEN

CSI CONTOUR SAND INJECTION

SPECIFICATIONS

ENGINE	Honda 20hp v-twin unleaded petrol key and recoil start
DRIVE	HYDROSTATIC forward/reverse variable speed
WHEELS	front - 16 x 6.00-6 tube type rear - 9 x 3.5-4 tube type
CUTTING DEPTH	variable from 0 to 1.5" (40mm)
CUTTING WIDTH	21" (525mm)
WIDTH	37" (950mm)
LENGTH	50" (1250mm)
HEIGHT	48" (1220mm)
WEIGHT	640lbs (290kg)
SANDBOX CAPACITY	165lbs (75kg)

BLADES

standard blade width and spacing
17 x 5/64" (2mm) blades at 1 1/4" (30mm) spacing

optional blade widths
3/64" (1mm) and 1/8" (3mm)

optional variable spacing when not injecting sand

tempered steel blades with eight tungsten tips
per blade

blades fitted in reverse rotation to slice cleanly
through the turf

deep scalloped design to prevent blades from
becoming clogged

A floating head pedestrian Graden with the ability to inject sand through a gravity feed system. Wider and faster than the GS04, it is ideal for level and undulating areas such as golf greens, approaches and lawns. Don't just groove it, fill it!



Cuts, fills and firms in one pass!



Material out, sand in



Blades in the floating head



Sand fills the grooves just millimeters behind the blades.

GRADEN INDUSTRIES PTY LTD
26-28 Scammel Street, Cambellfield
Victoria 3061, Australia
tel: 61 3 9305 3400
fax: 61 3 9305 3995
email: info@graden.com.au
www.graden.com.au
contact: Graham Dryden

GRADEN USA, INC.
7309 Capehart Road
Richmond, Virginia
tel: 804 249 9950
fax: 804 249 9951
email: info@gradenusa.com
www.gradenusa.com
contact: Matt Neal

