

Tacking Agent 3® Multi-Dimensional All-Purpose Tackifier

A tackifier that requires no cure time!

- Tacking Agent 3 has long set the standard as an effective binding agent. It is proven to reduce soil erosion and water runoff immediately after hydroseeding—no cure time is required!
- Tacking Agent 3 contains a flocculant, polyacrylamide and hydro-colloid polymers for enhanced fiber-to-soil bond as well as a marker dye to enhance visual metering when the product is being applied.



Typical Application Rates for ProPlus® Tacking Agent 3®

> 2H:1V Slope	60 lb/ac (67 kg/ha)
> 3H:1V and ≤ 2H:1V Slope	40 lb/ac (45 kg/ha)
≤ 3H:1V Slope	30 lb/ac (34 kg/ha)

Tank Loads	
300 gal (1,140 L)	3 lb (1.4 kg)
500 gal (1,890 L)	5 lb (2.3 kg)
900 gal (3,410 L)	10 lb (4.5 kg)
1,500 gal (5,680 L)	15 lb (6.8 kg)
3,000 gal (11,360 L)	30 lb (13.6 kg)

Packaging
7 – 3 lb (1.4 kg) water-soluble bags/case
4 – 8 lb (3.6 kg) bags/case
80 – 25 lb (11.3 kg) bags/pallet
40 – 50 lb (22.7 kg) bags/pallet

Amendment Ingredients
Polyacrylamide
Acrylamide copolymer
Hydro-colloid polymers
Marker Dye



For technical information or distribution, please call 800-508-8681.

For customer service, call 800-366-1180.

© 2022 PROFILE Products LLC. All rights reserved.

For warranty information, visit profileproducts.com.

750 W. Lake Cook Road • Suite 440 • Buffalo Grove, IL 60089

