

## DuraVeg Fibre Matrix

### 1 PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier:** DuraVeg Fibre Matrix  
**SDS Number:** AUCON117  
**Revision Date:** 2/2/2021  
**CAS Number:** Not applicable  
**Product Use:** Erosion control and revegetation mulch for hydraulic seeding.

**Supplier Details:** PROFILE Products, LLC  
750 LAKE COOK ROAD, SUITE 440  
BUFFALO GROVE, IL 60089

**Vendor Details:** PGG Wrightson Seeds LTD  
13 Felstead Drive  
Truganina, Victoria 3029

**Contact:** ChemTrec Acct #: CCN792719  
**Phone:** (847) 215-1144  
**Fax:** (847) 215-0577  
**Email:** tech@profileproducts.com  
**Internet:** www.profileproducts.com  
**Emergency:** Emergency Phone: (800) 424-9300  
(ChemTrec)

**Phone:** +61 9394 3400  
**Email:** info@pggwrightsonturf.com.au

Product Description: Green dyed wood fibres and a proprietary binder mixture.

### 2 HAZARDS IDENTIFICATION

#### Classification of Substance

**GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):**  
None, None, None

#### GHS Label Elements, Including Precautionary Statements

**GHS Signal Word:** NONE

**GHS Hazard Pictograms:**

No GHS pictograms indicated for this product

**GHS Hazard Statements:**

H000 - None

**GHS Precautionary Statements:**

No GHS precautionary statements indicated

#### Hazards not Otherwise Classified (HNOC) or not Covered by GHS

**Route of Entry:** Inhalation, skin contact, eye contact

**Inhalation:** Wood may cause sneezing, irritation, and dryness of the nose and throat. Dust may aggravate pre-existing respiratory conditions.

**Skin Contact:** Wood dust can cause irritation. Skin absorption is not known to occur.

**Eye Contact:** Wood dust can irritate the eyes.

**Ingestion:** No reports of human ingestion.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients:	
CAS#	% Chemical Name:
0	Hydrocolloidal Based Polysacchride Tackifier
9000-30-0	Guar gum
0	Proprietary Blend of Non-Hazardous Materials

4	<b>FIRST AID MEASURES</b>
---	---------------------------

**Inhalation:** Usually not a problem. Remove to fresh air if respiratory irritation develops, and get medical aid promptly if irritation persists.

**Skin Contact:** Usually not a problem. Wash off with running water if irritation is experienced.

**Eye Contact:** Open eyelids and flush with water.

**Ingestion:** Get medical attention.

5	<b>FIRE FIGHTING MEASURES</b>
---	-------------------------------

**Flammability:** Combustible product

**Flash Point:** Not applicable

**Flash Point Method:** Not applicable

**Autoignition Temp:** 200-260°C (400-500°F)

Conditions to avoid: In contact with flames or hot surfaces

Flammable- Extinguish with water;same as a wood fire

6	<b>ACCIDENTAL RELEASE MEASURES</b>
---	------------------------------------

Scoop up product. Wear goggles and respirator if dust is produced in unventilated areas. Wet product will be slippery.

7	<b>HANDLING AND STORAGE</b>
---	-----------------------------

**Handling Precautions:** Clean up areas where dust settles. Minimize blowdown or other practices that generate high airborne dust concentrations.

**Storage Requirements:** Store in a cool, dry place. Keep away from sources of ignition.

8	<b>EXPOSURE CONTROLS/PERSONAL PROTECTION</b>
---	--

**Engineering Controls:** None required for outdoor mixing and application. Use dust collection system for indoor handling operations.

**Personal Protective Equipment:** Eye Protection: Wear goggles when emptying bags and during other operations where there is a risk of dust entering the eyes.  
Gloves: Leather, plastic or rubber gloves could be worn to minimize skin irritation.  
Respirators: When handling methods generate dust at concentrations that exceed occupational exposure limits, wear a NIOSH approved respirator. A fabric respirator or a facepiece respirator with dust cartridges will generally provideadequate protection.  
Footwear: The product is slippery when wet. Wear appropriate footwear.

9	<b>PHYSICAL AND CHEMICAL PROPERTIES</b>
---	---

**Appearance:** Dyed green wood fibres - Pine & mixed hardwoods

**Physical State:** Wood Fibres **Odor:** Mild wood odor

**Specific Gravity or Density:** Lighter than water

**Vapor Pressure:** N/A

10	<b>STABILITY AND REACTIVITY</b>
----	---------------------------------

**Chemical Stability:** Stable product

**Conditions to Avoid:** Contact with strong acids and oxidizers may generate heat. Product may ignite at temperatures in excess of 200°C (400°F).

**Materials to Avoid:** Strong acids and oxidizers

**Hazardous Polymerization:** Will not occur.

11	<b>TOXICOLOGICAL INFORMATION</b>
----	----------------------------------

**EFFECTS OF CHRONIC EXPOSURE:**

Inhalation: Frequent and repeated exposure to wood dust is associated with an increased risk of developing nasal cancer.  
Skin Contact: Although rare, wood dust may cause dermatitis in sensitized people.

**Occupational Exposure Limits:**

Wood dusts- All other species: ACGIH (2007): TLV-TWA 1 mg/m<sup>3</sup> (Inhalable fraction); A4

Particulates Not Otherwise Regulated (PNOR): OSHA: PEL-TWA 15 mg/m<sup>3</sup> (Total Dust); 5 mg/m<sup>3</sup> (Respirable fraction)

Irritancy: Wood dust is a mild irritant  
Sensitization: Some wood dusts may cause allergic skin reactions

12	<b>ECOLOGICAL INFORMATION</b>
----	-------------------------------

Guar Gum (CAS# 9000-30-0) is listed as an inert ingredient permitted for use in nonfood use pesticide products by EPA. It is also classified under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA) as a minimal risk inert substance (List 4A) meaning that as a pesticide, Guar Gum is considered by the EPA to pose little or no risk to humans or the environment. The US Department of Agriculture (USDA) National Organic Program (NOP) also allows the use of Guar Gum in a variety of applications, but primarily as a pesticide in organic production operations. Finally, Guar Gum is listed on the Generally Recognized as Safe (GRAS) list by the Food and Drug Administration (FDA).

48-hr LC<sub>50</sub> = >100% for Daphnia magna when runoff generated using ASTM D7101 (2"/hr rainfall rate) was tested according to EPA-821-R-02-012.

13	<b>DISPOSAL CONSIDERATIONS</b>
----	--------------------------------

Normally can be disposed of as a wood residue. Ensure disposal is in compliance with local, provincial (state), and federal regulations.

14	<b>TRANSPORT INFORMATION</b>
----	------------------------------

Non-hazardous for air, sea and road freight.

15	<b>REGULATORY INFORMATION</b>
----	-------------------------------

Component (CAS#) [%] - CODES

-----  
Hydrocolloidal Based Polysacchride Tackifier (0) [n/a%]

Guar gum (9000-30-0) [n/a%] TSCA

Proprietary Blend of Non-Hazardous Materials (0) [n/a%]

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Regulatory CODE Descriptions

-----  
TSCA = Toxic Substances Control Act

**Disclaimer:**

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

Revision Date: 2/2/2021